

3					
	Example PN	Primary Features			
	8730-1535B + 3x 8720-1350B + 3x 8791B	Full remote and manual capable battery switches and VSR. Flying wires for installs not interested in sealed Deutsch style connectors			
	8830-1535B + 3x 8820-1350B + 2x 8791B	Full remote and manual capable battery switches and VSR. Individual DTM connectors for each relay if replacing legacy ML Series Relays			
	8830-2535B + 3x 8820-6350B + 2x 8791B	Full remote and manual capable battery switches and VSR. Single Deutsch DT connector helps error-proof production.			
	T 2X 0/91D	production.			

 Additional product variations available for Lithium Battery applications, no knobs in specific locations, and single wire pulse on/ pulse off control requirements. Contact Egis Mobile Electric for details.

## **Significant Benefits from XD Approach**

300 Amp capable VSR offer future-proof capability

Saves space/cost from fewer parts, less/shorter cables & fuses
Advanced VSR algorithm prevents cycling, optimizes charging

90% lower parasitic off-state power draw on average.

Remote switching discourages boaters from setting and leaving batteries combined, increasing safety afloat, and optimizing the longevity of the engine battery.

Fully adjustable VSR open & close settings

Robust manual override knob (vs susceptible BEP RBS knob)

VALUE ST-ERVISE SPECIFICS OMERGINE AND ST-ELLINE SPECIFICS (SS-E <sub>2</sub> /SS) AND SSEC ST-E <sup>2</sup> (SS) = 2.000 PROCESSES + E	OWNER	war	DAS	Eggs Mobile Bestric In 15 Mercer Ave, Son 162 Bellingham, NA 96225, USA
DO NOT SCALE DRAWING.	emicves			XD Relay - Five Battery, 3-4 Engine Example
	THE DAMPING OF METHOD IT ARE IN SPECIAL OF THE	THE BROTHSTON OF THE SECOND STATE OF T	CATACAGO COTOS COTOS	C INTS INTS INT 1 of 1

4

- 3

2

В